

## FA-SZ-U1

A solution for fiber optic subscriber networks.



Rack in a configuration for the FA-MP5 coupler



Rack in a configuration for the FA-MP1/FA-MP6 coupler



Rack with a coupler installed

### main features:

- ensures that the spare cable is laid with a safe bending radius;
- universal design for mounting the FA-MP1, FA-MP5, FA-MP6 series couplers;
- tool-free coupler mounting on the rack;
- fixing on a pole using steel tape;
- suitable for installation on a distance arm;
- possibility to use additional holders for subscriber cables mounted on the rack's arms (to be ordered separately);
- made of a material resistant to weather conditions, allowing many years of use.

### includes:

#### components to be ordered separately:

- universal mounting plate
- distance arm FA-PDSZ-20;
- adapter FA-SZ-A-FB for installation of Fibrain OBP-S8 coupler;
- subscriber cable holders FA-SZ-UA;
- stainless steel tape RM-S;
- clamp for steel tape RM-ZT.

### standards/certificates:

- EN485-1,2,4
- EN573-3
- EN15088
- ISO 9001:2015
- ISO 14001:2015

### market segments:



ISP AND CATV  
and MOBILE  
OPERATORS



DATA TRANSMISSION  
OPERATORS



ISP AND CATV  
OPERATORS



DESIGNERS  
AND CONTRACTORS



Installation manual  
(operation and  
maintenance document)

### technical parameters:

FA-SZ-U1	
dimensions [W x H x D] [mm]	600 x 600 x 110 (720 x 720 x 110 with subscriber cable holders)
weight [kg]	1
maximum spare cable capacity [m]	30 (for cable diameter 11 mm)
material	aluminum