

Singlemode Patchcord CONNECTICO

CO-X-XXX-XXX-2D-2,0-X-YE

Optical patchcord it is fibre optic section terminated on both side with connectors. Is an extension of the fiber optic path. Used to patch between fiber ports.



Patchcord CONNECTICO SMF SC/APC – SC/PC

features:

- patchcord SMF CONNECTICO,
- 2mm cable diameter

standards and certificates:

- IEC 61753-1
- IEC 61300-3-34
- IEC 61300-3-6
- ITU-T G.652D
- RoHS.

technical specifications:

Patchcord CONNECTICO SMF	APC	PC
insertion loss IL [dB]	< 0,3	< 0,3
return loss RL [dB]	> 65	> 45
durability	1000 mating cycles	1000 mating cycles
mechanical strength, load [N]	100	100
cable diameter[mm]	2,0	2,0
length [m]	0,5 – 100	0,5 – 100
fiber type acc. ITU-T	singlemode, G.652D	singlemode, G.652D
operating temperature [°C]	- 40 to +85	- 40 to +85
LSOH	yes	yes
cable colour	yellow	yellow
design	zirconia ceramic ferrule	zirconia ceramic ferrule

sectors:



Singlemode Patchcord CONNECTICO

CO-X-XXX-XXX-2D-2,0-X-YE

configuration:

code								description
CO-								patchcord CONNECTICO
	S-							patchcord simplex
	D-							patchcord duplex
		SCA-						SC/APC connector
		SCP-						SC/PC connector
		E2A-						E2000/APC connector
		E2P-						E2000/PC connector
		LCA-						LC/APC connector
		LCP-						LC/PC connector
		FCA-						FC/APC connector
		FCP-						FC/PC connector
		STP-						ST/PC connector
			SCA-					SC/APC connector
			SCP-					SC/PC connector
			E2A-					E2000/APC connector
			E2P-					E2000/PC connector
			LCA-					LC/APC connector
			LCP-					LC/PC connector
			FCA-					FC/APC connector
			FCP-					FC/PC connector
			STP-					ST/PC connector
				2D-				SMF G.652D
					2,0-			cable diameter 2 [mm]
						X-		length [m]
							YE	colour yellow

example:

CO2-D-SCA-SCP-2D-2,0-2-YE patchcord SM duplex SC/APC-SC/PC, G.652D, LSOH, 2,0mm, yellow, 2m.