


STZK series

Spare cable frames allow for safe organization of the cable reserve while maintaining their recommended bending radius.



Wall rack of the STZK series



Round column rack STZK series



Cable reserve frame with cover
STZK-60-N - rear view

main features:

- ensure that the cable reserve is laid maintaining a safe cable bend radius
- possibility of mounting on a wall, in a telecommunications chamber and on a pole
- possibility of winding up to 120 m of spare fiber optic cable with a diameter of 13.5 mm
- available versions with adjustable arms (550 - 750 mm) with a depth of 110 mm, 120 mm and 150 mm
- STZK-75C frame with double arm spacing adjustment and depth adjustment
- frame made of powder coated aluminium STZK-45-NA or STZK-60-NA dedicated for demanding environment,
- frames varnished with paint with increased resistance to external factors.

kit includes:

- mounting screws.

separately ordered options:

- frame cover P-STZK-60 or P-STZK-75.

standards and certificates:

- RoHS 2011/65/UE

sectors:



TELECOMMUNICATION
AND MOBILE
OPERATORS



DATA TRANSMISSION
OPERATORS



ISP AND CATV
OPERATORS



ENERGETICS



DESIGN AND EXECUTION
COMPANIES



DEVELOPERS



UNIVERSITIES



INTEGRATORS



MILITARY



RAILWAY

STZK series

technical specifications:

STZK-	45	60	69	75	75NA	75B	75C	90
width [mm]	450	600	Ø 690	750	550-750		550-750	900
height [mm]				120	110	150	130-200	120
depth [mm]	100	120	66	120	110	150	130-200	120
max length of cable Ø13,5 mm [m]	40	50	50	80	80	100	120	100
adjustable	-	-	-	-	yes	yes	yes	-
type	wall/pole mounting							
weight [kg]	~1	1,3	3,7	1,8	2,1	2,2	2,5	2,2

ordering:

code	description	
STZK-		spare cable frame
	45-	shoulder distance 450 mm, depth 120 mm
	60-	shoulder distance 600 mm, depth 120 mm
	NA	wall mounting, aluminum
	75-	shoulder distance 750 mm, depth 120 mm
	90-	shoulder distance 900 mm, depth 120 mm
	N	wall mounting
	NN	wall mounting, stainless
	69-	diameter 690 mm, depth 66 mm
	SO	round, pole mounting
	75A-	shoulder distance 750 mm, depth 110 mm
	75B-	shoulder distance 750 mm, depth 150 mm
	NR	wall mounting, adjustable shoulder distance 550 – 750 mm
	75C-	shoulder distance 750 mm, depth 150 mm
O-STZK-		spare cable frame with cover
	60-	shoulder distance 600 mm, depth 120 mm
	75-	shoulder distance 750 mm, depth 120 mm
	N	wall mounting