



## NODCO

NODCO series subscriber socket designed by FCA for use in residential and business FTTH network installations. Designed for high installation comfort and aesthetics with a proprietary utility model.



Subscriber socket, front + cover



Subscriber socket, rear + mounting plate

### main features:

- compact socket size for indoor use,
- wall mountable with a possibility of installation in a  $\varnothing$  60 mm flush mounted box ,
- snap-on socket cover,
- up to four fibre terminations possible,
- cable inputs on each side of the socket, also through the rear panel,
- separated part of cable input, fibre reserve and splicing,
- panel designed to ensure safe laying of the optical fibre,
- dedicated place for splice protection sleeve and 1x2 optical coupler,
- designated DAC cable input with offset lock,
- a mounting plate can be used for quick installation.

### basic set:

- pigtail and adapter as specified,
- wall mounting kit,
- mounting plate for  $\varnothing$  60 mm flush-mounted box, or wall mounting.

### options:

- subscriber patchcord.

### standards/certifications:

- fire rating UL-94 V-0
- RoHS
- IP40
- IK05
- design registered in the Patent Office under No. W.130284

### market segments:



TELECOMMUNICATIONS  
AND MOBILE OPERATORS



DATA TRANSMISSION  
OPERATORS



ISP AND CATV OPERATORS



DEVELOPERS



SYSTEM MANUFACTURERS  
AND INTEGRATORS



PUBLIC UTILITY  
COMPANIES

## NODCO

### technical parameters:

NODCO	
dimensions (W x H x D) [mm]*	80 x 80 x 25
number of cable inputs	8+2 (two inputs via rear panel)
max. number of thermal/mechanical splices	4/2
max. number of SC/LC duplex adapters	2
max. fibre length [m]	1
recommended coupler size (W x H x L) [mm]	4 x 4 x 40
connector IL insertion loss [dB]	≤ 0.25
connector RL return loss [dB]	≥ 65
connector type	SC, LC
fibre type	G.657A2
socket/mounting plate material	ABS/ABS
socket colour / mounting plate colour	RAL 9016
socket IP/IK protection rating	IP40/IK05
storage temperature [°C]	-30 to +85
installation/operation temperature [°C]	-20 to +75
weight [g]**	40

\* socket dimensions without mounted adapter

\*\* socket weight without pigtail, adapter

## NODCO

### SC/APC subscriber socket:

code	description
NODCO-A-S-000-SCA-7A2-0,9-1-WH	NODCO subscriber socket, equipped, SC/APC adapter with cover, SC/APC pigtail G.657A2 length 1m
NODCO-2A-2S-000-SCA-7A2-0,9-1-WH	NODCO subscriber socket, equipped, 2x SC/APC adapter with cover, 2x SC/APC pigtail G.657A2 length 1m
NODCO-1x2-2A-S-000-2SCA-7A2-0,9-1-WH	NODCO subscriber socket, equipped, 1x2 coupler, 2x SC/APC adapter with cover, 2x SC/APC pigtail G.657A2 length 1m

### LC/APC subscriber socket:

code	description
NODCO-A-2S-000-LCA-7A2-0,9-1-WH	NODCO subscriber socket, equipped, LC/APC duplex adapter with cover, 2x LC/APC pigtail G.657A2 length 1m
NODCO-4A-S-000-LCA-7A2-0,9-1-WH	NODCO subscriber socket, equipped, 2x LC/APC duplex adapter with cover, 4x LC/APC pigtail G.657A2 length 1m

### build your set:

code	description
S-SCA-SCA-S1-7B3-2.8-1.5-WH	SC/APC-SC/APC subscriber patchcord, SM, Standard, G.657B3, LSOH, 2.8mm, 1.5m, White
S-SCA-SCA-S1-7B3-2.8-3-WH	SC/APC-SC/APC subscriber patchcord, SM, Standard, G.657B3, LSOH, 2.8mm, 3m, White
S-SCA-SCA-S1-7B3-2.8-5-WH	SC/APC-SC/APC subscriber patchcord, SM, Standard, G.657B3, LSOH, 2.8mm, 5m, White
S-LCA-LCA-S1-7B3-2.8-1.5-WH	LC/APC-LC/APC subscriber patchcord, SM, Standard, G.657B3, LSOH, 2.8mm, 1.5m, White
S-LCA-LCA-S1-7B3-2.8-3-WH	LC/APC-LC/APC subscriber patchcord, SM, Standard, G.657B3, LSOH, 2.8mm, 3m, White
S-LCA-LCA-S1-7B3-2.8-5-WH	LC/APC-LC/APC subscriber patchcord, SM, Standard, G.657B3, LSOH, 2.8mm, 5m, White
S-PL-102-TUBE-900-NC/SCA	1x2 PLC coupler, mini metal box (4x4x40), G.657A2, 0.9mm, 1m, input without connectors, output - 2x SC/APC, output - 2x SC/APC